

250-system (25 t)

V250

- fitted with safety device in the form of a protective cover
- working pressure 63 MPa (630 bar)
- crimp force 250 kN (25 tonnes)
- light and versatile steel crimp head

Crimp head for contact crimping Cu terminals, type KRF/KSF 10-800 mm², Al terminals 16-630 mm² (-300 solid), C sleeves 6/6-300/300 mm². Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-250000**

EAN: **7393487035911**

Crimp geometries: **Punch, Hexagonal, Oval**

Safety device: **Protective cover**

Working pressure (MPa): **63**

Quick connector: **Yes**

AWG/MCM Stranded Al: **6 AWG - 1250 MCM**

AWG/MCM Solid Al: **6 AWG - 550 MCM**

AWG/MCM Cu: **8 AWG - 1600 MCM**

mm² Stranded Al: **16-630**

mm² Solid Al: **16-300**

mm² Cu: **10-800**

Crimp range Cu-terminals min (mm²): **10**

Crimp range Cu-terminals max (mm²): **800**

Crimp range C-connectors min (mm²): **6**

Crimp range C-connectors max (mm²): **300**

Crimp range Al-terminals min (mm²): **16**

Crimp range Al-terminals max (mm²): **630**



Image not found or type unknown