

# KRFS185-10

- Material: Cu 99.95%, tin plated Cu/Sn.
- Inspection hole
- For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.
- Easy to install via cable gland, allows for pre-installation.
- The width of the palm is less than or as wide as the neck.
- UL-approved, DNV approved.



## Example of marking KRFS: 17 (neck) Elpress logotype 70 10F (palm)

17 = Die no. 70 = mm<sup>2</sup> 10 = palm hole for M10 F = type KRF for stranded and flexible conductors.

Tube terminal with narrow palm for multi-stranded (class 5) and stranded (class 2) Cu conductors (acc. to IEC 60228), 185 mm<sup>2</sup>, with an M10 hole in the palm. Used with Elpress certified systems V1300 or V250.



Item number: **7301-292100**

EAN: **7393487062115**

W (mm): **27**

t (mm): **6.6**

N (mm): **11**

N1 (mm): **13**

P (mm): **24**

f (mm): **1**

d (mm): **21**

D (mm): **27**

L (mm): **79**

s (mm): **37**

Screw: **M10**

Inspection hole: **Yes**

AWG/MCM Cu: **350 MCM**

mm<sup>2</sup> Cu: **185**