

Shearbolt terminals 10 - 630 mm<sup>2</sup> (pre-assembled screw)

# SL240N-10-12

- shearbolt material: brass for minimum friction
- threaded shear-off shearbolts for easy handling
- voltage range 1 kV
- meets the requirements of IEC standard 61238-1:2003
- the terminals are of the bimetallic type for best functionality



Shearbolt terminal 1 kV that is suitable for both Al and Cu class 1 and class 2 cable. Round cable 120-240 mm<sup>2</sup>, sector shaped cable 120-240 mm<sup>2</sup>. Suitable for both M10 and M12, reduction washer and flat washer are included when ordering.



Item number: **7334-017000**

EAN: **7393487083554**

a (mm): **13**  
W (mm): **31.5**  
t (mm): **7.6**  
N (mm): **15**  
d (mm): **25**  
D (mm): **38/33,1**  
L1 (mm): **86**  
L (mm): **144.5**  
s (mm): **76**  
L2 (mm): **31**

Screw: **M12, M10**

Max voltage (kV): **1**

Screen conductor (with filling piece), Min (mm<sup>2</sup>): **29-146 (SC240/PEN)**

Screen conductor (with filling piece), Max (mm<sup>2</sup>): **29-146 (SC240/PEN)**

Cable type Round (mm<sup>2</sup>): **120-240**

Cable type Sector (mm<sup>2</sup>): **120-240**