

KRF angled terminals 90°, 10 - 185 mm<sup>2</sup>

# KRF70-12-90GR

- Material: Cu 99.95%, tin plated Cu/Sn.
- Inspection hole.
- For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.
- UL-approved, DNV approved.

## Example of marking KRF: 17 (neck) Elpress logo 70 10F (palm)

17 = Die No. 70 = mm<sup>2</sup> 10 = palm hole for M10 F = type KRF for stranded and flexible conductors.

Angled tube terminal 90° for multi-stranded (class 5) and stranded (class 2) Cu conductors (acc. to IEC 60228), 70 mm<sup>2</sup>, with an M12 hole in the palm. Used with Elpress certified systems V600, V1300, V250.



Item number: **7301-116600**

EAN: **7393487016477**

A (mm): **31.5**  
W (mm): **24**  
t (mm): **3.9**  
N (mm): **12.5**  
N1 (mm): **19.5**  
P (mm): **32**  
d (mm): **13**  
D (mm): **17**  
s (mm): **22**

Screw: **M12**

Angle (°): **90**

Inspection hole: **Yes**

AWG/MCM Cu: **2/0 AWG**

mm<sup>2</sup> Cu: **70**