

1300-system (H)

V1311-A

- fast-forward feed system
- crimp force 130 kN
- ergonomic handle
- easy to carry and work with
- no need for external power source
- requires low handle force, approx 245 N at max force

Tested and certified hydraulic hand-held tool for contact crimping Cu terminals, type KRF/KSF 10-400 mm², Al terminals 16-400 mm² (-240 solid), C sleeves 6/6-120/120 mm².



Item number: **5202-131000**

EAN: **7393487000476**

Fast forward function: **Yes**

Ratchet function that does not trigger until completed crimp: **Yes**

Delivery box: **Plywood box**

Working temperature, Min (°C): **-22**

Working temperature, Max (°C): **55**

Crimp geometries: **Punch, Hexagonal, Oval**

AWG/MCM Stranded Al: **6 AWG - 700 MCM**

AWG/MCM Solid Al: **6 AWG - 450 MCM**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm² Stranded Al: **16-400**

mm² Solid Al: **16-240**

mm² Cu: **10-400**

Crimp range Cu-terminals min (mm²): **10**

Crimp range Cu-terminals max (mm²): **400**

Crimp range C-connectors min (mm²): **6**

Crimp range C-connectors max (mm²): **120**

Crimp range Al-terminals min (mm²): **16**

Crimp range Al-terminals max (mm²): **400**



Image not found or type unknown