

MINI (0-3,5 t)

PVL350

- Crimping force max. 35 kN
- Slim crimping head – perfect for tight spaces
- High-performance 12 V Li-Ion battery with indication of charge status
- Opening, rotating “flip top” head for easy die replacement and good accessibility
- Easy to use with one hand thanks to its ergonomic 2-component housing with grip-friendly protection
- Automatic return of the dies

Elpress mini tool PVL350, electro-hydraulic crimping tool 6-70 mm².



Item number: **5204-010500**

EAN: **7393487059849**

Delivery box: **Plastic case**

Working temperature, Min (°C): **-10**

Working temperature, Max (°C): **40**

Crimp geometries: **Hexagonal, Oval**

Charger: **Li-ion**

Charge time (min): **40**

Battery: **10,8V, 2,0Ah Li-Ion**

No. of batteries: **1**

Crimps/charge: **100-150 depending on size and temperature**

AWG/MCM Cu: **12 - 2/0 AWG**

mm² Cu: **4-70**

mm² C-sleeve Cu Range, Min: **12**

mm² C-sleeve Cu Range, Max: **50**

mm² KR/KS, KRF/KSF: **4-70**

mm² KRT/KST: **10-70**

mm² KRD/KSD: **4-95**

Crimp range C-connectors min (mm²): **12**

Crimp range C-connectors max (mm²): **50**



Image not found or type unknown