

KRFS Rørkabelsko 50 - 400 mm² med smal laske, KRFS tube terminals 50 - 400 mm² with narrow palm, KRFS tube terminals 50 - 400 mm² with narrow palm

KRFS50-6

- Material: Cu 99.95%, tin plated Cu/Sn.
- Inspection hole
- For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.
- Easy to install via cable gland, allows for pre-installation.
- The width of the palm is less than or as wide as the neck.
- UL-approved, DNV approved.



Example of marking KRFS: 17 (neck) Elpress logotype 70 10F (palm)

17 = Die no. 70 = mm² 10 = palm hole for M10 F = type KRF for stranded and flexible conductors.

Tube terminal with narrow palm for multi-stranded (class 5) and stranded (class 2) Cu conductors (acc. to IEC 60228), 50 mm², with an M6 hole in the palm.

Used with Elpress certified systems V600, V1300, V250.



Item number: **7301-290300**

EAN: **7393487061941**

W (mm): **15**

t (mm): **4**

N (mm): **11**

N1 (mm): **11.5**

P (mm): **22.5**

f (mm): **1.25**

d (mm): **11**

D (mm): **14,5**

L (mm): **51**

s (mm): **19**

Screw: **M6**

Inspection hole: **Yes**

AWG/MCM Cu: **1/0 AWG**

mm² Cu: **50**

