


# AKS120-70

- Connector from Al conductor to Cu conductor.
- Stranded/solid Al conductors, stranded/multi-stranded Cu conductors.
- For multi-stranded Cu conductors, contact crimping using the Dual system is recommended.
- Two crimps are required for Al, normally one for Cu.



AlCu through connector, from Al conductor to Cu conductor. For stranded Al cable 120 mm<sup>2</sup>, or for solid Al cable 150 mm<sup>2</sup>, to stranded/multi-stranded Cu cable 70 mm<sup>2</sup>. When crimping the Cu section, place the dies between the mark on the sleeve and the edge of the Cu section. Used with Elpress certified systems V1300, V250.



Item number: **7333-401600**

EAN: **7393487009837**

s1 (mm): **25**

d (mm): **14**

D (mm): **25**

L (mm): **93**

s (mm): **61**

d1 (mm): **13**

D1 (mm): **17**

AWG/MCM Stranded Al: **250 MCM**

AWG/MCM Solid Al: **300 MCM**

AWG/MCM Cu: **2/0 AWG**

mm<sup>2</sup> Stranded Al: **120**

mm<sup>2</sup> Solid Al: **150**

mm<sup>2</sup> Cu: **70**

Screen conductor (mm<sup>2</sup>): **72-88**