

KRF angled terminals 45°

# KRF95-12-45GR

- Material: Cu 99.95%, tin plated Cu/Sn.
- Inspection hole
- For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.

- UL-approved, DNV approved.



## Example of marking KRF: 17 (neck) Elpress logo 70 10F (palm)

17 = Die No. 70 = mm<sup>2</sup> 10 = palm hole for M10 F = type KRF for stranded and flexible conductors.

Angled tube terminal 45° for multi-stranded (class 5) and stranded (class 2) Cu conductors (acc. to IEC 60228), 95 mm<sup>2</sup>, with an M12 hole in the palm. Used with Elpress certified systems V600, V1300, V250.



Item number: **7301-127500**

EAN: **7393487016255**

A (mm): **40**  
W (mm): **28**  
t (mm): **4.9**  
N (mm): **12.5**  
N1 (mm): **19.5**  
P (mm): **32**  
d (mm): **15**  
D (mm): **20**  
s (mm): **25**

Screw: **M12**  
Angle (°): **45**  
Inspection hole: **Yes**

AWG/MCM Cu: **3/0 AWG**  
mm<sup>2</sup> Cu: **95**