

KRFS tube terminals 50 - 400 mm<sup>2</sup> with narrow palm

# KRFS300A-16

- Material: Cu 99.95%, tin plated Cu/Sn.
- Inspection hole
- For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.
- Easy to install via cable gland, allows for pre-installation.
- The width of the palm is less than or as wide as the neck.
- UL-approved, DNV approved.



## Example of marking KRFS: 17 (neck) Elpress logotype 70 10F (palm)

17 = Die no. 70 = mm<sup>2</sup> 10 = palm hole for M10 F = type KRF for stranded and flexible conductors.

Tube terminal with narrow palm for multi-stranded (class 5) and stranded (class 2) Cu conductors (acc. to IEC 60228), 300 mm<sup>2</sup>, with an M16 hole in the palm. Used with Elpress certified systems V1300 or V250.



Item number: **7301-293100**

EAN: **7393487062184**

W (mm): **31**  
t (mm): **8.6**  
N (mm): **20**  
N1 (mm): **19**  
P (mm): **39**  
f (mm): **1.25**  
d (mm): **24.5**  
D (mm): **31,5**  
L1 (mm): **79**  
L (mm): **99**  
s (mm): **40**

Screw: **M16**

Inspection hole: **Yes**

AWG/MCM Cu: **550 MCM**

mm<sup>2</sup> Cu: **300**

